



INDUCTIVE PROXIMITY SWITCH				
Structural category		Angular column type		
Outward appearance code		<b>LMF37</b>		
Appearance				
Dimension				
Flush	Detection distance		15mm	
	DC 6	NPN	NO	3015NA
			NC	3015NB
			NO+NC	3015NC
	~ 36	PNP	NO	3015PA
			NC	3015PB
			NO+NC	3015PC
	V	two wire system	NO	3015LA
			NC	3015LB
	AC 90 ~ 250 V	SRC Control label silicon	NO	2015A
			NC	2015B
			NO+NC	2015C
Relay output		2015JC		
Non-Flush	Detection distance		20mm	
	DC 6	NPN	NO	3020NA
			NC	3020NB
			NO+NC	3020NC
	~ 36	PNP	NO	3020PA
			NC	3020PB
			NO+NC	3020PC
	V	two wire system	NO	3020LA
			NC	3020LB
	AC 90 ~ 250 V	SRC Control label silicon	NO	2020A
			NC	2020B
			NO+NC	2020C
Relay output		2020JC		
Control output	DC	200mA		
	SCR/Relay	300mA/2A		
Output voltage dropDC/AC		DC≤1.5V /DC(Two wire system)≤5V/ AC≤TV		
Consumption current		DC≤1mA/ DC(Two wire system)≤13mA /AC≤2mA		
Standard detected object		50×50×1(A3 iron)		
Repeated precision		0.05		
DC/AC Response frequency		200Hz/25Hz		
Working environment temperature		-25℃~75℃		
Insulation resistance		50MΩ		
Shell material		ABS Resin		
Protection grade		IEC standard IP67		
Alternative model at home and abroad		HY-A20□		