



INDUCTIVE PROXIMITY SWITCH				
Structural category		Angular column type		
Outward appearance code		<b>LMF6</b>		
Appearance				
Dimension				
Push	Detection distance		8mm	
	DC 6	NPN	NO	3008NA
			NC	3008NB
			NO+NC	3008NC
	~ 36	PNP	NO	3008PA
			NC	3008PB
			NO+NC	3008PC
	V	two wire system	NO	3008LA
			NC	3008LB
	AC 90	SRC Control label silicon	NO	2008A
			NC	2008B
			NO+NC	
	~ 250			
	V	Relay output		
Non-Push	Detection distance		10mm	
	DC 6	NPN	NO	3010NA
			NC	3010NB
			NO+NC	3010NC
	~ 36	PNP	NO	3010PA
			NC	3010PB
			NO+NC	3010PC
	V	two wire system	NO	3010LA
			NC	3010LB
	AC 90	SRC Control label silicon	NO	2010A
			NC	2010B
			NO+NC	
	~ 250			
	V	Relay output		
Control output	DC		200mA	
	SCR/Relay		300mA	
Output voltage dropDC/AC		DC<3V AC<10V		
Consumption current		DC<15mA AC<10mA		
Standard detected object		30×30×1(A3 iron)		
Repeated precision		0.05		
DC/AC Response frequency		200Hz/25Hz		
Working environment temperature		-25℃~75℃		
Insulation resistance		50MΩ		
Shell material		ABS Resin		
Protection grade		IEC standard IP67		
Alternative model at home and abroad		TL-N10M□		